

PROJECT:

COMMENTS:

DATA SHEET.

EXTREME CONDITION LED LOW BAY FIXTURE

DETAILS.

- Extreme Condition LED Low Bay Fixture - IP65 - Exterior Waterproof
- UL Certified
- 3 Year Warranty
- Vandal resistant exterior housing
- Low profile, swivel bracketed mounting
- Ideal for low mounting height applications, manufacturing areas, warehouses, parking garages, tunnel lighting.



SPECIFICATIONS.

MODEL :	E-FTN/SC/LB/0.6M/ Colour	E-FTN/SC/LB/1M/ Colour	E-FTN/SC/LB/1.2M/ Colour	E-FTN/SC/LB/1.5M/ Colour
DIMENSIONS (MM) :	72 x 105 x 600mm	72 x 105 x 1003mm	72 x 105 x 1203mm	72 x 105 x 1503mm
DIMENSIONS (INCHES) :	2.8 x 4.1 x 23.6"	2.8 x 4.1 x 39.5"	2.8 x 4.1 x 47.4"	2.8 x 4.1 x 59.2"
POWER LOAD :	30 W	55 W	70 W	80 W
KELVIN (CCT) :	3000K 4100K 5800K	3000K 4100K 5800K	3000K 4100K 5800K	3000K 4100K 5800K
COLOUR :	WARM NEUTRAL COOL	WARM NEUTRAL COOL	WARM NEUTRAL COOL	WARM NEUTRAL COOL
LUMEN OUTPUT :	2250 Lm 2580 Lm 2640 Lm	4560 Lm 4950 Lm 5060 Lm	5810 Lm 6300 Lm 6440 Lm	6640 Lm 7200 Lm 7360 Lm
POWER FACTOR :	>0.9	>0.9	>0.9	>0.9
INPUT VOLTAGE :	100~240VAC, 50/60Hz	100~240VAC, 50/60Hz	100~240VAC, 50/60Hz	100~240VAC, 50/60Hz
IP RATING :	IP65	IP65	IP65	IP65

EXTREME OUTPUT MODEL AVAILABLE:

EXTREME OUTPUT (Lm) :	2490 Lm 2700 Lm 2760 Lm	5250 Lm 6020 Lm 6160 Lm	6000 Lm 6880 Lm 7040 Lm	6985 Lm 7735 Lm 7910 Lm
-----------------------	-----------------------------	-----------------------------	-----------------------------	-----------------------------

DIMENSIONS. (INSTALLATION METHOD DRAWINGS AVAILABLE UPON REQUEST)

