

Sustainable LED Lighting Solutions...

DATA SHEET.

HIGH OUTPUT LED LIGHTBAR

COVERED UNDER A 2 YEAR WARRANTY.

Our low profile eLume LED Light Bars provide an energy efficient solution to traditional fluorescent lighting. Impervious to shock and vibrations combined with an IP65 rating our high brightness, eLume LED Light Bars are ideal in replacing fragile fluorescent tubes.

With their durable life (up to 50,000 hours), energy efficiency and their ability to function in extreme temperatures, our eLume LED Light Bars are well suited for refrigerator, display, exhibit, under-cabinet, task, cove and back lighting applications.

- Covered under a 2 year warranty
- Dimmable (Optional)
- Available in various lengths
- Indoor or outdoor applications
- Adjustable angle w/ swivel bracket
- Minimal heat output (Safe to the touch)
- Water resistant
- No mercury or harmful toxins
- Emits no UV or IR radiation
- No maintenance costs
- Long life (Up to 50,000 hours)
- Energy efficient - Low power consumption
- Low voltage
- Uniform light output
- Easy to install (Magnetic/adhesive/Bracket)
- Available in Warm White or Cool White
- Low profile & light weight
- Daisy-chainable (Custom lead lengths)

SPECIFICATIONS.

MODEL :	E-HOLB/xx (xx = Length)
AVAILABLE COLOURS :	NEUTRAL WHITE - 5300 °K WARM WHITE - 3500 °K
POWER CONSUMPTION :	SEE CHART BELOW
OPERATING VOLTAGE :	12V
TEMPERATURE RANGE :	(> -50 °C) , (< 55°C)
RATED LIFESPAN :	OVER 50,000 HOURS
DIMENSIONS :	0.7" x 0.4" x LENGTH (WxHxL)
IP RATING :	IP65
DIODES :	0.25W NICHIA LEDS

SPECIFIC MODEL INFORMATION.

Model #	Dimensions (LxWxH)	Wattage	Lumen @ 5300 °K
E-HBLB/11	11.8" x 0.7" x 0.4"	4.5W	360 lm
E-HBLB/22	22.8" x 0.7" x 0.4"	9W	720 lm
E-HBLB/33	33.9" x 0.7" x 0.4"	13.5W	1080 lm
E-HBLB/39	39.4" x 0.7" x 0.4"	15.8W	1264 lm
E-HBLB/44	44.9" x 0.7" x 0.4"	18W	1440 lm
E-HBLB/55	55.9" x 0.7" x 0.4"	22.5W	1800 lm

CONTACT INFO.

www.elumanation.com
416.225.6400 - Toronto area

info@elumanation.com
1750 Plummer Street, Unit 18
Pickering, ON, Canada. L1W 3L7

